# 915 MHz Liquid Heating Microwave System for Chemicals, Fluids, & Pumpable Foods

With its unique application of highintensity electromagnetic energy to pumpable foods, beverages and biomaterials, Industrial Microwave Systems (IMS) has solved the problem of "hot spots" often associated with traditional surface heating technologies. For a pasteurization or sterilization process, the benefits of ultra-rapid in-line microwave heating include:

- Higher product quality resulting from greater retention of color, taste, texture and nutrients.
- Longer production runs due to the reduction of scale or burn-on from hot surface processes.
- Reduced costs of system sterilization and cleaning.
- Rapid deactivation of enzymes such as polyphenol oxidase (PPO) that reduce product shelf life.
- Due to the volumetric ionic heating process, the center of any particulates may reach a higher temperature than the surrounding fluid. As this is the exact opposite of what occurs when using conventional surface heaters, it enhances thermal processing and food safety.



### **Applications**

The IMS In-Line Microwave heater is particularly effective for the thermal processing of high value, heat and/or shear sensitive, high viscosity, and multi-phase foods, including:

- Fruit purees with/without particulates
- Meat and poultry emulsions
- Nutraceuticals
- Pasta and other high acid based sauces
- Salsa and tomato based products
- Surimi
- Vegetable purees with / without particulates



#### **ABOUT IMS**

Industrial Microwave Systems, (IMS) is a wholly owned subsidiary of Microwave Techniques LLC, a private company based in Gorham, Maine with decades of success in the innovation, design, and construction of food processing equipment. IMS is also partnered with Ferrite and MEGA to provide additional access to microwave system and component technology across the globe.

#### **IMS PRODUCTS**

IMS offers a series of modularized benchtop and commercial in-line heaters, available with 915 or 2,450 MHz microwave generators or transmitters. These standardized equipment modules can be connected in series, parallel, or a combination as plant design and production needs change or expand. IMS single mode applicators insure a uniform field is focused and located at the exact position as the product flowing through the heating tube.

#### **CONTACT**

To request additional information, please contact:

Microwave Techniques, LLC Systems Division

104 Perimeter Road Nashua, NH 03060 Tel: (603) 881-5234

www.microwavetechniques.com



## 915 MHz, 100 kW MICROWAVE SYSTEM OPERATING PARAMETERS PER MODULE:

Single Module Process  Specification	Commercial
Max. Throughput	10 GPM (2, 500 kg/hour)
Max. Temperature	302°F (150°C)
Max. Pressure	150 psig (10.5 Barg)

Design Options	Commercial
Generator Frequency	915 MHz
Applicator Material	Stainless Steel
Product Tube*	PTFE with Ceramic
	Pressure Sleeve
Tube Size	1.5" (38mm) to 2.5"
	(63mm)
Standard Tube Fitting	Stainless Tri-Clamp
	Ferrule
* Other FDA approved materials available	

Generator, Control Panel & Applicator Dimensions	Commercial
Length	6'0" (1.83m), 2'8" (0.81m), 2'9" (0.84m)
Width	2'6" (0.76m), 0'9" (0.23m), 2'0" (0.61m)
Height	9'3" (2.82m), 4'0" (1.22m), 8'2" (2.49m)

Utilities	Commercial
Power Output	75 – 200 kW
Electricity	90-240 kW
Magnetron	27 GPM (100 LPM) /
Cooling Water+	100 kW Generator

Actual Process Performance and Specifications will depend on the throughput, properties, and heating range of product.







